




UCT 309-28 F

Slider bearing housing unit T type, Cast iron housing, Set screw locking spherical ball bearing, T type seal

Техническая информация



Основные размеры и рабочие параметры

d	44.45mm	Внутренний диаметр (отверстие)
K	125mm	Guide groove distance
L	138mm	Общая длина
T	90mm	Height of bearing seat fixed side
A	55mm	Pocket height
n	22mm	channel distance
C	18mm	Guide groove width
B	38mm	Bearing seat width
Bi	57mm	Total width
H4	97mm	Guide groove length
H3	178mm	Whole length
H2	24mm	Pocket width
H1	20mm	Fixed link length
H	110mm	Axis distance
N	34mm	Fixing holes
N1	55mm	Width of bearing seat fixed side
≈m	4Kg	weight
UCT309-28F	Bearing Type	
T309-28	Bearing seat model	
M6*1	Oil injection hole	
J7	Assembly torque	
HT200	Bearing seat material	

*数据表仅为所选产品的尺寸和基本额定载荷概览。请始终遵守本产品的所有更多信息和指南。您可通过我们网站上的联系表了解更多信息。

Контакты: E-mail: mr.suo@zrbearing.net

Тел.: 0319-5628888

Адрес: Китай, пров. Хэбэй, уезд Линьси,
северная сторона кольцевой дороги Чэнбэй —
Zhongda Bearing