




UCT 210-30 F

Slider bearing housing unit T type, Cast iron housing, Set screw locking spherical ball bearing, T type seal

Техническая информация



Основные размеры и рабочие параметры

d	47.625mm	Внутренний диаметр (отверстие)
K	102mm	Guide groove distance
L	117mm	Общая длина
T	83mm	Height of bearing seat fixed side
A	49mm	Pocket height
n	19mm	channel distance
C	16mm	Guide groove width
B	37mm	Bearing seat width
Bi	51.6mm	Total width
H4	86mm	Guide groove length
H3	149mm	Whole length
H2	19mm	Pocket width
H1	16mm	Fixed link length
H	90mm	Axis distance
N	29mm	Fixing holes
N1	49mm	Width of bearing seat fixed side
≈ m	2.54Kg	weight
UCT10-30F		Bearing Type
T210-30		Bearing seat model
M6*1		Oil injection hole
J7		Assembly torque
HT200		Bearing seat material

*数据表仅为所选产品的尺寸和基本额定载荷概览。请始终遵守本产品的所有更多信息和指南。您可通过我们网站上的联系表了解更多信息。

Контакты: E-mail: mr.suo@zrbearing.net

Тел.: 0319-5628888

Адрес: Китай, пров. Хэбэй, уезд Линьси,
северная сторона кольцевой дороги Чэнбэй —
Zhongda Bearing